

AT A GLANCE

APPARATUS CASTORS

we move your life



What is the best way to transport my goods from one place to another? Sure, on CASCOO castors. But which castors do I actually need for my purpose? Various influences should be taken into account when choosing the right wheels: load capacity, temperature range, ground surface, noise characteristics, working environment and of course the price. In the following we would like to provide you an overview that can be used as a guide to help you make your decision.



Two or rather four swivel castors?

Regardless of whether you use two swivel and two fixed castors or prefer four swivel castors, both versions have their right to exist. If you have to cover long distances with your transport trolley, we recommend equipping it with two swivel and two fixed castors, as the fixed castors ensure stable straight running and the user does not have to constantly correct the direction of movement. If you have to transport your goods in narrow aisles (e.g. shopping trolleys in the supermarket), the version with four swivel castors is the right choice, as you are so flexible in lateral movements and can turn on your heel.



How do I calculate the maximum load capacity?

When using four castors under a transport trolley, you must always assume that one castor is „hanging“ in the air - due to an uneven floor for example - and cannot contribute to the stability of the trolley. Therefore, the total load capacity of a trolley is always calculated with 3 out of 4 castors. The details of the load capacity on the following pages always refer to the dynamic properties of the respective DIN standards (EN 12530 - 12533) per castor. If you multiply these values by 3, you get the total load capacity of the trolley according to the corresponding DIN standard and its requirements.



When do I need a braked version?

A distinction is usually made between a total brake, which blocks the direction and the run of a castor, and a directional lock, where the wheel is still moving but in terms of alignment „only“ works like a fixed castor. The most common type of lock is the total lock (or double stop). It is very important to note that this is not working as a real brake, but as a lock, which only secures the transport trolley against rolling away. We guarantee the functionality here under the following definition:

combination of two fixed castors - one swivel castor - one swivel castor with total lock

- securing of an empty or loaded transport trolley against rolling away on basically level surfaces, but with a maximum gradient of 2%
- securing of an empty or loaded transport trolley against rolling away in light winds
- short-term detection of an empty or loaded transport trolley on truck lifting platforms in combined use with the roll-off protection of the lift

Combination of two fixed castors – two swivel castors with total brakes

- securing of an empty or loaded transport trolley against rolling away on surfaces with a maximum gradient of 5%
- securing of an empty or loaded transport trolley against rolling away in strong winds (does not protect against overturning of the trolley)
- detection of an empty or loaded roll container in the truck in combination with legally compliant load securing. As far as possible, the brakes should not be activated in the moving truck

[The operator is obliged to carry out the operation taking into account the applicable legislation]

HOW TO MAKE YOUR right choice



Which material do I choose for my purpose?

Probably the most difficult question when choosing your right choice of suitable castors is the question of the material. Each material has different properties and accordingly different advantages and disadvantages as well. Material can be soft or hard, loud or quiet, solid or light and much more. On the following pages we will bring you closer to the advantages of each series and hope to be able to support you with your decision. If you have unanswered questions, please do not hesitate to contact us. On the one hand, we are happy to provide with help and advice due to many years of experience, on the other hand you may also need a special solution, which we would be happy to explain to you in a personal conversation.

APPARATUS CASTORS

Apparatus castors are mainly used for the transport of light to medium-duty equipment indoors. They convince with optimal stability, low rolling resistance, noise-reduction and high mobility.

Apparatus castors are often used in display constructions, medical devices, intralogistics or on catering equipment. These castors are available with plate attachment and bolt hole attachment in different dimensions.

Optionally available with expander, stem or threaded screw fixation

EXPANDER OVERVIEW

Expander round tube



	type	inner diameter	screw dimension	material
EXRO1921	round tube 19.0 mm-21.5 mm	11 mm	M10x90	aluminium / nylon
EXRO2124	round tube 21.5 mm-24.0 mm	11 mm	M10x90	aluminium / nylon
EXRO2427	round tube 24.0 mm-27.0 mm	11 mm	M10x90	aluminium / nylon
EXRO2730	round tube 27.0 mm-30.0 mm	11 mm	M10x90	aluminium / nylon
EXRO3135	round tube 31.0 mm-35.0 mm	11 mm	M10x90	aluminium / nylon

Expander square tube



	type	inner diameter	screw dimension	material
EXSQ2124	square tube 21.5 mm-24.0 mm	11 mm	M10x90	aluminium / nylon
EXSQ2427	square tube 24.0 mm-27.0 mm	11 mm	M10x90	aluminium / nylon
EXSQ2730	square tube 27.0 mm-30.0 mm	11 mm	M10x90	aluminium / nylon
EXSQ3135	square tube 31.0 mm-35.0 mm	11 mm	M10x90	aluminium / nylon
EXSQ3640	square tube 36.0 mm-40.0 mm	11 mm	M10x90	aluminium / nylon

DIFFERENT KIND OF STEMS WITH CIRCLIP OR THREADED STEMS ON REQUEST



APPARATUS CASTORS AT A GLANCE



SERIES P2T2

PP / TPR
light apparatus

page 6



SERIES P4P4

PP
light apparatus

page 8



SERIES P2T2

PP / TPR
plain bearing

page 10



SERIES P2T2

PP / TPR
ball bearing

page 12



SERIES P2T2

PP / TPR
with expander

page 14



SERIES P2T2

PP / TPR
twin wheel castors

page 16



SERIES N4N4

PP
twin wheel castors

page 18



SERIES P2T2

rim: polypropylene
 tread: thermoplastic rubber 95° shore A grey
 axle bearing: plain bearing / ball bearing
 threadguard: without / full covering plastic threadguard
 load capacity: 50 kg to 75 kg
 wheel diameter: 50 mm to 100 mm
 temperature range: -20°C to +60°C



swivel castor

								
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg]
SAPA9C0050P2T2P0N		050	60x60	48/39x48/39	6.3	25	70	50
SAPA9C0050P2T2B42		050	60x60	48/39x48/39	6.3	25	70	50
SAPA2C0075P2T2P0N		075	60x60	48/38x48/38	6.3	25	100	75
SAPA2C0075P2T2B42		075	60x60	48/38x48/38	6.3	25	100	75



fixed castor

FAPBCC0050P2T2P0N		050	55x55	44/38.5x44/38.5	6.3		70	50
FAPBCC0050P2T2B42		050	55x55	44/38.5x44/38.5	6.3		70	50
FAPCCC0075P2T2P0N		075	67x60	48/38x48/38	6.3		100	75
FAPCCC0075P2T2B42		075	67x60	48/38x48/38	6.3		100	75



swivel castor with total brake

TAPA9C0050P2T2P0N		050	60x60	48/39x48/39	6.3	25	70	80	50
TAPA9C0050P2T2B42		050	60x60	48/39x48/39	6.3	25	70	80	50
TAPA2C0075P2T2P0N		075	60x60	48/38x48/38	6.3	25	100	80	75
TAPA2C0075P2T2B42		075	60x60	48/38x48/38	6.3	25	100	80	75

EXAMPLE FOR APPLICATION

- ✓ display construction and shopfitting
- ✓ medical equipment
- ✓ catering equipment (cutlery trolleys)

HIGHLIGHTS AND ADVANTAGES

- ✓ noise-reduced running on all surfaces
- ✓ ideal load capacities designed for the application
- ✓ ball bearing as axle bearing for improved rolling resistance



bolt hole swivel castor

		 [mm]	 [mm]		 [mm]	 [mm]	 [mm]	 [kg]
HAH19C0050P2T2P0N		050	11		25	70		50
HAH19C0050P2T2B42								
HAH12C0075P2T2P0N		075	11		25	100		75
HAH12C0075P2T2B42								
HSH12C0100P2T2P0N		100	11		32	122		60



bolt hole swivel castor with total brake

		 [mm]	 [mm]		 [mm]	 [mm]	 [mm]	 [kg]
BAH19C0050P2T2P0N		050	11		25	70	80	50
BAH19C0050P2T2B42								
BAH12C0075P2T2P0N		075	11		25	100	80	75
BAH12C0075P2T2B42								
BSH12C0100P2T2P0N		100	11		24	122	80	60



single wheel

		 [mm]	 [mm]	 [mm]	 [mm]	 ø		 [kg]
050P2T2P0N		050	19	22	8	M6		50
050P2T2B42					6			
075P2T2P0N		075	25	28	8	M6		75
075P2T2B42					6			
100P2T2P0N-28		100	25	28	8	M6		60





SERIES P4P4

rim: polypropylene
 tread: polypropylene black
 axle bearing: plain bearing
 threadguard: without
 load capacity: 30 kg
 wheel diameter: 50 mm to 75 mm
 temperature range: -20°C to +60°C



swivel castor

									
		[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg]
SAPA9C0050P4P4P0N	≡	050	60x60	48/39x48/39	6.3	25	70		30
SAPA2C0075P4P4P0N	≡	075	60x60	48/38x48/38	6.3	25	100		30



fixed castor

FAPBCC0050P4P4P0N	≡	050	55x55	44/38.5x44/38.5	6.3		70		30
FAPCCC0075P4P4P0N	≡	075	67x60	48/38x48/38	6.3		100		30



swivel castor with total brake

TAPA9C0050P4P4P0N	≡	050	60x60	48/39x48/39	6.3	25	70	80	30
TAPA2C0075P4P4P0N	≡	075	60x60	48/38x48/38	6.3	25	100	80	30

EXAMPLE FOR APPLICATION

- ✓ display construction and shopfitting
- ✓ medical equipment
- ✓ catering equipment (cutlery trolleys)

HIGHLIGHTS AND ADVANTAGES

- ✓ economical design for simple applications
- ✓ ideal load capacities designed for the application
- ✓ flexible everyday helper



		 [mm]	 [mm]		 [mm]	 [mm]	 [mm]	 [kg]
bolt hole swivel castor								
	HAH19C0050P4P4P0N	050	11		25	70		30
	HAH12C0075P4P4P0N	075	11		25	100		30



		 [mm]	 [mm]		 [mm]	 [mm]	 [mm]	 [kg]
bolt hole swivel castor with total brake								
	BAH19C0050P4P4P0N	050	11		25	70	80	30
	BAH12C0075P4P4P0N	075	11		25	100	80	30



		 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [kg]
single wheel							
	050P4P4P0N	050	13	22	6	M6	30
	075P4P4P0N	075	23	28	8	M6	30



SERIES P2T2

rim: polypropylene
 tread: thermoplastic rubber 95° shore A grey
 axle bearing: plain bearing
 threadguard: without
 load capacity: 80 kg to 100 kg
 wheel diameter: 80 mm to 150 mm
 temperature range: -20°C to +60°C



swivel castor

		 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [kg]
SAP5C0080P2T2P0N	≡	080	77x67	61.5/56x51.5/46.5	8.5	37	111		80
SAP5C0100P2T2P0N	≡	100	77x67	61.5/56x51.5/46.5	8.5	37	135		100
SAP5C0125P2T2P0N SAPJ5C0125P2T2P0N	≡	125	77x67 95x70	61.5/56x51.5/46.5 75x50	8.5 11	40	160		100
SAP5C0150P2T2P0N	≡	150	77x67	61.5/56x51.5/46.5	8.5	40	185		100



fixed castor

FAPE5C0080P2T2P0N	≡	080	77x67	61.5/56x51.5/46.5	8.5		111		80
FAPE5C0100P2T2P0N	≡	100	77x67	61.5/56x51.5/46.5	8.5		135		100
FAPE5C0125P2T2P0N FAPJ5C0125P2T2P0N	≡	125	77x67 95x70	61.5/56x51.5/46.5 75x50	8.5 11		160		100
FAPE5C0150P2T2P0N	≡	150	77x67	61.5/56x51.5/46.5	8.5		185		100



swivel castor with total brake

TAPE5C0080P2T2P0N	≡	080	77x67	61.5/56x51.5/46.5	8.5	37	111	132	80
TAPE5C0100P2T2P0N	≡	100	77x67	61.5/56x51.5/46.5	8.5	37	135	132	100
TAPE5C0125P2T2P0N TAPJ5C0125P2T2P0N	≡	125	77x67 95x70	61.5/56x51.5/46.5 75x50	8.5 11	40	160	132	100
TAPE5C0150P2T2P0N	≡	150	77x67	61.5/56x51.5/46.5	8.5	40	185	132	100

EXAMPLE FOR APPLICATION

- ✓ display construction and shopfitting
- ✓ medical equipment
- ✓ catering equipment (cutlery trolleys)

HIGHLIGHTS AND ADVANTAGES

- ✓ noise-reduced running on all surfaces
- ✓ ideal load capacities designed for the application
- ✓ large diameters up to 150 mm



bolt hole swivel castor

		 [mm]	 [mm]		 [mm]	 [mm]	 [mm]	 [kg]
HAH15C0080P2T2P0N	==	080	11		37	111		80
HAH15C0100P2T2P0N	==	100	11		37	135		100
HAH15C0125P2T2P0N	==	125	11		40	160		100
HAH15C0150P2T2P0N	==	150	11		40	185		100



bolt hole swivel castor with total brake

		 [mm]	 [mm]		 [mm]	 [mm]	 [mm]	 [kg]
BAH15C0080P2T2P0N	==	080	11		37	111	132	80
BAH15C0100P2T2P0N	==	100	11		37	135	132	100
BAH15C0125P2T2P0N	==	125	11		40	160	132	100
BAH15C0150P2T2P0N	==	150	11		40	185	132	100



single wheel

		 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [kg]
080P2T2P0N	==	080	32	36	12	M8		80
100P2T2P0N	==	100	32	36	12	M8		100
125P2T2P0N	==	125	32	36	12	M8		100
150P2T2P0N	==	150	32	36	12	M8		100



SERIES P2T2

rim: polypropylene
 tread: thermoplastic rubber 95° shore A grey
 axle bearing: ball bearing
 threadguard: full covering plastic threadguard
 load capacity: 80 kg to 100 kg
 wheel diameter: 80 mm to 150 mm
 temperature range: -20°C to +60°C



swivel castor

	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg]
SAPE5C0080P2T2B42		080	77x67	61.5/56x51.5/46.5	8.5	37	111		80
SAPE5C0100P2T2B42		100	77x67	61.5/56x51.5/46.5	8.5	37	135		100
SAPE5C0125P2T2B42 SAPJ5C0125P2T2B42		125	77x67 95x70	61.5/56x51.5/46.5 75x50	8.5 11	40	160		100
SAPE5C0150P2T2B42		150	77x67	61.5/56x51.5/46.5	8.5	40	185		100



fixed castor

FAPE5C0080P2T2B42		080	77x67	61.5/56x51.5/46.5	8.5		111		80
FAPE5C0100P2T2B42		100	77x67	61.5/56x51.5/46.5	8.5		135		100
FAPE5C0125P2T2B42 FAPJ5C0125P2T2B42		125	77x67 95x70	61.5/56x51.5/46.5 75x50	8.5 11		160		100
FAPE5C0150P2T2B42		150	77x67	61.5/56x51.5/46.5	8.5		185		100



swivel castor with total brake

TAPE5C0080P2T2B42		080	77x67	61.5/56x51.5/46.5	8.5	37	111	132	80
TAPE5C0100P2T2B42		100	77x67	61.5/56x51.5/46.5	8.5	37	135	132	100
TAPE5C0125P2T2B42 TAPJ5C0125P2T2B42		125	77x67 95x70	61.5/56x51.5/46.5 75x50	8.5 11	40	160	132	100
TAPE5C0150P2T2B42		150	77x67	61.5/56x51.5/46.5	8.5	40	185	132	100

EXAMPLE FOR APPLICATION

- ✓ display construction and shopfitting
- ✓ medical equipment
- ✓ catering equipment (cutlery trolleys)

HIGHLIGHTS AND ADVANTAGES

- ✓ noise-reduced running on all surfaces
- ✓ ideal load capacities designed for the application
- ✓ ball bearing as axle bearing for improved rolling resistance



bolt hole swivel castor

							
	[mm]	[mm]		[mm]	[mm]	[mm]	[kg]
HAH15C0080P2T2B42		080	11		37	111	80
HAH15C0100P2T2B42		100	11		37	135	100
HAH15C0125P2T2B42		125	11		40	160	100
HAH15C0150P2T2B42		150	11		40	185	100



bolt hole swivel castor with total brake

								
	[mm]	[mm]		[mm]	[mm]	[mm]	[kg]	
BAH15C0080P2T2B42		080	11		37	111	132	80
BAH15C0100P2T2B42		100	11		37	135	132	100
BAH15C0125P2T2B42		125	11		40	160	132	100
BAH15C0150P2T2B42		150	11		40	185	132	100



single wheel

							
	[mm]	[mm]	[mm]	[mm]	∅		[kg]
080P2T2B42		080	32	36	8	M8	80
100P2T2B42		100	32	36	8	M8	100
125P2T2B42		125	32	36	8	M8	100
150P2T2B42		150	32	36	8	M8	100



SERIES P2T2

rim: polypropylene
 tread: thermoplastic rubber 95° shore A grey
 axle bearing: plain bearing / ball bearing
 threadguard: without / full covering plastic threadguard
 load capacity: 80 kg to 100 kg
 wheel diameter: 80 mm to 150 mm
 temperature range: -20°C to +60°C



bolt hole swivel castor		[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg]
HAX15C0080P2T2P0N	==	080	11	19-35	37	111			80
HAX15C0100P2T2P0N	==	100	11	19-35	37	135			100
HAX15C0125P2T2P0N	==	125	11	19-35	40	160			100
HAX15C0150P2T2P0N	==	150	11	19-35	40	185			100



bolt hole swivel castor with total brake									
BAX15C0080P2T2P0N	==	080	11	19-35	37	111	132		80
BAX15C0100P2T2P0N	==	100	11	19-35	37	135	132		100
BAX15C0125P2T2P0N	==	125	11	19-35	40	160	132		100
BAX15C0150P2T2P0N	==	150	11	19-35	40	185	132		100

EXAMPLE FOR APPLICATION

- ✓ display construction and shopfitting
- ✓ medical equipment
- ✓ catering equipment (cutlery trolleys)

HIGHLIGHTS AND ADVANTAGES

- ✓ noise-reduced running on all surfaces
- ✓ ideal load capacities designed for the application
- ✓ ball bearing as axle bearing for improved rolling resistance



bolt hole swivel castor

		 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [kg]
HAX15C0080P2T2B42		080	11	21.5-40	37	111		80
HAX15C0100P2T2B42		100	11	21.5-40	37	135		100
HAX15C0125P2T2B42		125	11	21.5-40	40	160		100
HAX15C0150P2T2B42		150	11	21.5-40	40	185		100



bolt hole swivel castor with total brake

BAX15C0080P2T2B42		080	11	21.5-40	37	111	132	80
BAX15C0100P2T2B42		100	11	21.5-40	37	135	132	100
BAX15C0125P2T2B42		125	11	21.5-40	40	160	132	100
BAX15C0150P2T2B42		150	11	21.5-40	40	185	132	100



SERIES P2T2

rim: polypropylene
 tread: thermoplastic rubber 95° shore A grey
 axle bearing: plain bearing / ball bearing
 threadguard: without / full covering plastic threadguard
 load capacity: 70 kg to 100 kg
 wheel diameter: 50 mm to 75 mm
 temperature range: -20°C to +60°C



swivel castor

		 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [kg]
SDPE6C0050P2T2P0N	≡	050	60x60	48/38x48/38	6.3	25	70		70
SDPE6C0050P2T2B42	≡	050	60x60	48/38x48/38	6.3	25	70		70
SDPE1C0075P2T2P0N	≡	075	77x67	61.5/56x51.5/46.5	8.5	32	100		100
SDPE1C0075P2T2B42	≡	075	77x67	61.5/56x51.5/46.5	8.5	32	100		100



swivel castor with total brake

		[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	[kg]
TDPE6C0050P2T2P0N	≡	050	60x60	48/38x48/38	6.3	25	70	80	70
TDPE6C0050P2T2B42	≡	050	60x60	48/38x48/38	6.3	25	70	80	70
TDPE1C0075P2T2P0N	≡	075	77x67	61.5/56x51.5/46.5	8.5	32	100	96	100
TDPE1C0075P2T2B42	≡	075	77x67	61.5/56x51.5/46.5	8.5	32	100	96	100



single wheel

		 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [kg]
050P2T2P0N	≡	050	19	22	8	M6			50
075P2T2P0N	≡	075	25	30	10	M8			75



single wheel

		[mm]	[kg]						
050P2T2B42	≡	050	19	22	6	M6			50
075P2T2B42	≡	075	25	30	8	M8			75

EXAMPLE FOR APPLICATION

- ✓ display construction and shopfitting
- ✓ medical equipment
- ✓ catering equipment (cutlery trolleys)

HIGHLIGHTS AND ADVANTAGES

- ✓ noise-reduced running on all surfaces
- ✓ higher load capacities by splitting on twin wheels
- ✓ can be combined with different stems or expanders



bolt hole swivel castor

		 [mm]	 [mm]		 [mm]	 [mm]	 [mm]	 [kg]
HDHHHC0050P2T2P0N	≡	050	11		25	70		70
HDHHHC0050P2T2B42	≡	050	11		25	70		70
HDHJJC0075P2T2P0N	≡	075	11		32	100		100
HDHJJC0075P2T2B42	≡	075	11		32	100		100



bolt hole swivel castor with total brake

BDHHHC0050P2T2P0N	≡	050	11		25	70	80	70
BDHHHC0050P2T2B42	≡	050	11		25	70	80	70
BDHJJC0075P2T2P0N	≡	075	11		32	100	96	100
BDHJJC0075P2T2B42	≡	075	11		32	100	96	100



bolt hole swivel castor

HDXHHC0050P2T2P0N	≡	050	11		25	70		70
HDXHHC0050P2T2B42	≡	050	11		25	70		70
HDXJJC0075P2T2P0N	≡	075	11		32	100		100
HDXJJC0075P2T2B42	≡	075	11		32	100		100



bolt hole swivel castor with total brake

BDXHHC0050P2T2P0N	≡	050	11		25	70	80	70
BDXHHC0050P2T2B42	≡	050	11		25	70	80	70
BDXJJC0075P2T2P0N	≡	075	11		32	100	96	100
BDXJJC0075P2T2B42	≡	075	11		32	100	96	100



SERIES N4N4

rim: polyamide
 tread: polyamide black
 axle bearing: plain bearing
 threadguard: without
 load capacity: 70 kg
 wheel diameter: 50 mm to 75 mm
 temperature range: -20°C to +60°C



swivel castor

		 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [mm]	 [kg]
SDPE6C0050N4N4P0N	≡	050	60x60	48/38x48/38	6.3	25	70	70
SDPE1C0075N4N4P0N	≡	075	77x67	61.5/56x51.5/46.5	8.5	32	100	70



swivel castor with total brake

TDPE6C0050N4N4P0N	≡	050	60x60	48/38x48/38	6.3	25	70	80	70
TDPE1C0075N4N4P0N	≡	075	77x67	61.5/56x51.5/46.5	8.5	32	100	96	70



single wheel

		 [mm]	 [mm]	 [mm]	 [mm]	 ∅	 [kg]
050N4N4P0N	≡	050	18	22	8	M6	70
075N4N4P0N	≡	075	23	28	8	M8	70

EXAMPLE FOR APPLICATION

- ✓ display construction and shopfitting
- ✓ medical equipment
- ✓ catering equipment (cutlery trolleys)

HIGHLIGHTS AND ADVANTAGES

- ✓ cheaper nylon option
- ✓ higher load capacities by splitting on twin wheels
- ✓ can be combined with different stems or expanders



		 [mm]	 [mm]		 [mm]	 [mm]	 [mm]	 [kg]
bolt hole swivel castor								
HDHHHC0050N4N4P0N	==	050	11		25	70		70
HDHJJC0075N4N4P0N	==	075	11		32	100		70



		[mm]	[mm]		[mm]	[mm]	[mm]	[kg]
bolt hole swivel castor with total brake								
BDHHHC0050N4N4P0N	==	050	11		25	70	80	70
BDHJJC0075N4N4P0N	==	075	11		32	100	96	70



		[mm]	[mm]		[mm]	[mm]	[mm]	[kg]
bolt hole swivel castor								
HDXHHC0050N4N4P0N	==	050	11		25	70		70
HDXJJC0075N4N4P0N	==	075	11		32	100		70



		[mm]	[mm]		[mm]	[mm]	[mm]	[kg]
bolt hole swivel castor with total brake								
BDXHHC0050N4N4P0N	==	050	11		25	70	80	70
BDXJJC0075PN4N4P0N	==	075	11		32	100	96	70



Distribution Europe

CASCOO Europe GmbH

Lütke Haar 15
59602 Rùthen
Germany
+49 (0) 2952 9706290
info@cascoo.eu
www.cascoo.eu

Production China

Zhongshan CASCOO Metal Machinery Co.,Ltd.

No.108 Zhaoyi road
Dongsheng Town, Zhongshan, Guangdong, China
Post Code: 528414
+86 (0) 760 89821559
sales@cascoo.com
www.cascoo.com

